



TYPE 2

10/20/10
SODERSTROM

| REVISIONS | 1 | 2 | 3 | 4 | 5 | 6 |
|-----------|-----------------|------------|----------------|------------------|--------------------|--------------------|
| | 03/22/10 | 03/23/10 | 03/21/10 | 04/05/10 | 04/16/10 | 10/20/10 |
| | EAVE HEIGHT DFM | SCADA SIZE | SCADA LOCATION | ADD UTILITY ROOM | MOVE CONF. WINDOWS | ADDED NEW FEATURES |

Figure 8b: O&M Facility Plan and Profile

FLOOR PLAN O&M BUILDING PROTOTYPE DESIGN

INDICATES INTERIOR DEFINING WALL. 6" 20 GA STUDS @ 24" O/C. SOUND ATTENUATION Batts ONE LAYER OF 1/2 GYP. BOARD EA SIDE.

ALL EXTERIOR DOORS TO BE 3'X7' HT. INTERIOR DRG TO BE 3'X7' S.C. WOOD ALL IN HM FRAMES



ALL EXTERIOR DOORS TO BE 3'X7' HT. INTERIOR DRG TO BE 3'X7' S.C. WOOD ALL IN HM FRAMES

SITE GRADING, ACCESSIBLE PARKING PAD, APPROX. SITE CIVIL, LIGHTING, AND FENCING PER MOST RECENT O&M BUILDING SPECIFICATIONS.

PROVIDE ELECTRICAL LOADS, EMERGENCY SYSTEMS, LIGHTING AND PUMPING PER MOST RECENT O&M BUILDING SPECIFICATIONS.

UP. STP. CEILING AT 8'-0" PROVIDE ADA APPROVED GRABS BARS, DEFLECTION FIXTURES, PROTECTION HARDWARE, ETC. FOR LAV.

HYVAC EQUIPMENT TANKLESS WATER HEATER, WELL TANK & CONTROL WATER FILTER IN UTILITY

PLUMB FOR REFR. ICE MAKER, SINK, DISHWASHER, ELEC. FOR MICROWAVE, ETC. PROVIDE 1/2-HIGH PANEL EX CABINETRY COUNTER